

GSM/GRRS-Module





SIM900

SIMCom presents an ultra compact and reliable wireless module-SIM900. This is a complete Quad-band GSM/GPRS module in a SMT type and designed with a very powerful single-chip processor integrating AMR926EJ-S core, allowing you to benefit from small dimensions and cost-effective solutions.

Featuring an industry-standard interface, the SIM900 delivers GSM/GPRS 850/900/1800/1900MHz performance for voice, SMS, Data, and Fax in a small form factor and with low power consumption. With a tiny configuration of 24mm x 24mm x 3 mm, SIM900 can fit almost all the space requirements in your M2M applications, especially for slim and compact demands of design.

Smart Machine Smart Decision

General features

- •Quad-Band 850/ 900/ 1800/ 1900 MHz
- •GPRS multi-slot class 10/8
- •GPRS mobile station class B
- •Compliant to GSM phase 2/2+
- Class 4 (2 W @850/ 900 MHz)
- Class 1 (1 W @ 1800/1900MHz)
- •SAIC (Single Antenna Interference Cancellation) support
- •Dimensions: 24* 24 * 3 mm
- •Weight: 3.4g
- •Control via AT commands (GSM 07.07,07.05 and
- SIMCOM enhanced AT Commands)
- •SIM application toolkit
- •Supply voltage range: 3.2 ... 4.8V
- •Low power consumption: 1.0mA(sleep mode&BS-PA-
- MFRMS=9)
- •Operation temperature: -40° C to +85° C

Specifications for Fax

•Group 3, class 1

Specifications for GPRS Data

- •GPRS class 10: max. 85.6 kbps (downlink)
- •PBCCH support
- •Coding schemes CS 1, 2, 3, 4
- •PPP-stack

Specifications for CSD Data

- •CSD up to 14.4 kbps
- •USSD
- •Non transparent mode

Specifications for SMS via GSM/GPRS

- •Point to point MO and MT
- •SMS cell broadcast
- •Text and PDU mode

Software features

- •0710 MUX protocol
- •Embedded TCP/UDP protocol
- •FTP/HTTP
- •FOTA (available at Q3 2010)
- •MMS (available at Q3 2010)
- •Embedded AT (available at Q3 2010)

Specifications for Voice

- Tricodec
- Half rate (HR)
- Full rate (FR)
- Enhanced Full rate (EFR)
- AMR
- Half rate (HR)
- Full rate (FR)
- •Hands-free operation (Echo suppression)

Interfaces

- •Interface to external SIM 3V/ 1.8V
- Analog audio interface
- •RTC backup
- •SPI interface (option)
- Serial interface
- •Antenna pad
- •I2C
- •GPIO
- •PWM
- •ADC

Compatibility

•AT cellular command interface

Approvals:

•CE •IC
•FCC •ICASA
•ROHS •TA
•PTCRB •REACH
•GCF •OCD

Approvals (on going):

•AT&T

More about SIMCom SIM900

Please contact: Tel: 86-21-32523300

Fax: 86-21-32523301 Email: simcom@sim.com Website: www.sim.com/wm

All specifications are subject to change without prior notice.